



• 1227 PUTMAN DRIVE • HUNTSVILLE, AL •
•(256) 837-1526 • WWW.ANDERSPOOL.COM •

FLOCCULANT PROCEDURE

1. Backwash or clean filter if necessary.
2. Adjust PH to 7.5-8.0 for best results.
3. Turn pump off.
4. Move multi-port handle to the "Recirculate" or "Whirlpool" position.
5. Remove skimmer basket and any product in skimmer
6. Turn pump on.
7. Use Bioguard® Powerfloc at a rate of 8oz per 10,000 gallons
8. Shake product well.
9. Pour Powerfloc directly into skimmer.
10. Allow to circulate 2-4 hours
11. Turn pump off for 24-48 hours or until debris settles.
12. Vacuum settled debris out to WASTE.
13. Reapply if needed.

If your filter does not have a "Recirculate" or "Whirlpool" position:

1. Backwash or clean filter if necessary.
2. Adjust PH to 7.5-8.0 for best results.
3. Turn pump off.
4. Remove skimmer basket and any product in skimmer
5. Turn pump on.
6. Use Bioguard® Powerfloc at a rate of 8oz per 10,000 gallons
7. Shake product well.
8. Dilute Powerfloc 8oz/1 Gallon of water in a clean water bucket. ** NEVER add water to Powerfloc, always Powerfloc to water
9. Apply evenly over the surface of the pool.
10. Allow to circulate 2-4 hours
11. Turn pump off for 24-48 hours or until debris settles.
12. Vacuum settled debris out to WASTE.
13. Reapply if needed.